

STX 5000C

Mobile terminal for forklifts and loaders



Wireless communication module

Bracket used for mounting on forklifts

Housing made of brushed stainless steel



Clear TFT monochromatic display of very high brightness - enabling operation even in bright sunlight

Membrane keypad

STX 5000C

Mobile terminal for forklifts and loaders

TECHNICAL SPECIFICATION

CATEGORY	PARAMETER
COMMUNICATION INTERFACE	
Type of communication interface	RS 232, RS 485, Ethernet
Galvanic isolation of the communication port	Yes (1 kV)
Number of digital inputs	4
Number of digital outputs	4
Timer outputs	Yes
Display	TFT high-brightness
UNICODE character support	Yes
Display character height	From 5 to 60 mm
CHARACTERISTIC	
Housing material	Stainless steel
Dimensions of the housing	225/150/100 mm
Keypad type	Membrane
External power supply	12~24 VDC
Holder for mounting on a forklift	Yes
ENVIRONMENTAL LIMITS AND CONFORMITY TO STANDARDS	
Storage temperature	From -30 to +70 C
Operating temperature	From -20 to +60 C
Relative humidity	< 95% without condensation
Electromagnetic compatibility	CE

ORDERING INFORMATION	
PRODUCT	ORDERING KEY
STX 5000C	HDW-STX-5000C

* The manufacturer reserves itself the right to amend product features. Product parameters may be amended without any prior notice.
Please find more information at www.gs-software.pl